

Leica CR50

Communication Unit

Datasheet



The Leica CR50 communication unit supports an internal cellular modem and a dual-frequency radio. The Leica CR50 can be connected to the Leica iCON gps 100 and Leica iCON gps 120 on-machine GNSS receivers to perform high-accuracy RTK GNSS positioning.

Features

- Bluetooth®
- 2 x M12 automotive ethernet communication ports
- Optional integrated dual-frequency UHF radio (400 MHz and 900 MHz)¹⁾
- Integrated worldwide cellular modem (UTMS/LTE)
- Diversity modem antenna support

Benefits

- Simple and clean installation with a minimal number of parts and cables, thanks to the automotive Ethernet support.
- Customers can easily change between 400 MHz and 900 MHz with the integrated dual frequency radio ¹⁾.
- Web interface for convenient access for software configuration.

leica-geosystems.com



- when it has to be **right**

Leica
Geosystems

Leica CR50 Communication Unit



HARDWARE SPECIFICATIONS

Weight	842 g (1.86 lbs)
Dimensions	150 mm x 150 mm x 40 mm (5.90 x 5.90 x 1.57 in)

ENVIRONMENTAL SPECIFICATIONS

Operating temperature	-40 °C to +65 °C (-40 °F to +149 °F)
Storage temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Humidity	IEC60068-2-78, +65 °C; 92%, IEC60068-2-30; Test Db; Variant 1 +55 °C; 95%; +25 °C; 95%
Water/dust rating	IP6K8/6K9K according to ISO 20653
Vibration	IEC 60068-2-6; Test Fc, 5-500 Hz; 5 g; ±15 mm MIL-STD-810G, Fig. 514.6E-1; Category 24
Shock	IEC 60068-2-27, 60 g; 6 ms
Drops	Withstands 1.0 m drop onto hard surfaces

POWER & ELECTRICAL

Supply voltage	Range 9 – 36 V DC
Power consumption	NTRIP Rover, radio excluded: 7.2 W typically, 24 V @ 300 mA
Certifications	Compliance to: FCC/IC, CE

COMMUNICATION

Communication ports	• 1 x USB M8, 1 x automotive Ethernet M12 T male power-in/data • 1 x automotive Ethernet M12 T female power-out/data • 1 x TNC for external radio antenna • 2 x SMA for external modem antenna
---------------------	--

BUILT-IN DATA LINKS

UHF radio	• Optional integrated radio • Dual frequency ¹⁾ • SATEL TR489: 403–473 MHz; PacCrest 4FSK, GMSK & FST, Trimtalk 450s T & P, Satel 3AS, 8FSK & 16FSK; 902–928 MHz (license-free in North America)
UHF radio antenna	External antenna connector (Type TNC)
4G LTE / 3G HSPA / HSPA+ / WCDMA / TD-SCDMA / UMTS / Cellular modem	Built-in cellular modem as default User-exchangeable SIM card 18-Band LTE: Band 1, 2, 3, 4, 5, 7, 8, 9, 12, 13, 18, 19, 20, 26, 28, 29, 30, 41 8-Band UMTS (WCDMA / HSPA+): Band 1, 2, 4, 5, 6, 8, 9, 19 Up to 600 Mbps downlink speed, up to 150 Mbps uplink speed
Cellular modem antenna	2x external antenna connector (Type SMA)
Bluetooth®	Bluetooth v5.0 class 2

COMMUNICATION PROTOCOLS

Real-time data formats	Leica, Leica 4G, CMR, CMR+, RTCM2.3, RTCM 3.1, RTCM 3.2 MSM 1-7
Web based protocol	NTRIP and TCP Client

INTERFACE

LED status indicator	3 x LED for power, Internet and UHF radio status (if applicable)
----------------------	--

¹⁾ Only valid for USA & Canada